




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>4</sup> :  B66F 9/065	A1	(11) International Publication Number: WO 89/ 00972 (43) International Publication Date: 9 February 1989 (09.02.89)
(21) International Application Number: PCT/EP88/00647 (22) International Filing Date: 19 July 1988 (19.07.88) (31) Priority Application Number: 53559 B/87 (32) Priority Date: 27 July 1987 (27.07.87) (33) Priority Country: IT (71) Applicant (for all designated States except US): MERLO S.P.A. INDUSTRIA METALMECCANICA [IT/IT]; S.S. 22 Cuneo-Dronero, 9, I-12020 Frazione San Defendente di Cervasca (IT). (72) Inventors; and (75) Inventors/Applicants (for US only): MERLO, Amilcare [IT/IT]; Via S. Maurizio, 26, I-12100 Cuneo (IT). GALFRE', Renato [IT/IT]; Via Tesoriere, 90, I-12011 Borgo San Dalmazzo (IT).	(74) Agents: JACOBACCI, Filippo et al.; Jacobacci-Casetta & Perani S.p.A., Via Alfieri, 17, I-10121 Torino (IT). (81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), SU, US. Published With international search report.	

(54) Title: A LIFTING TRUCK WITH A TELESCOPIC LIFTING ARM



## (57) Abstract

In a lifting truck of the type comprising a wheeled structure carrying a lifting arm (22) articulated to the rear of the structure and a cab (10) situated on one side of the structure at one side of the longitudinal axis (A-A) of the structure, the internal combustion engine (16) which propels the truck and operates the arm is disposed in a housing (12) which is situated on the opposite side of the longitudinal axis to the cab (10) and is spaced from the cab so as to form therewith a space (14) at least as wide as the lifting arm (22). The arm (22) is articulated to the structure of the truck in such a position that, in its completely lowered position, it is partly housed in the space so as not to interfere with the view of the operator working in the driving cab.

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
AU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	LI	Liechtenstein	SN	Senegal
CH	Switzerland	LK	Sri Lanka	SU	Soviet Union
CM	Cameroon	LU	Luxembourg	TD	Chad
DE	Germany, Federal Republic of	MC	Monaco	TG	Togo
DK	Denmark	MG	Madagascar	US	United States of America
FI	Finland				

- 1 -

A lifting truck with a telescopic lifting arm

The present invention relates to a lifting truck of the type comprising a wheeled structure carrying a telescopic lifting arm articulated to the rear of the structure about a horizontal axis perpendicular to the longitudinal axis of the truck, an internal combustion engine supported by the structure for the propulsion of the truck and for the operation of the arm, and a driving and operating cab situated on one side of the structure to one side of the longitudinal axis of the structure.

Lifting trucks of the aforementioned type generally have the disadvantage that they do not provide sufficient visibility to the side and to the rear for the operator working in the operating and driving cab. In fact, in lifting trucks currently available on the market, the lifting arm is articulated on an axis which is perpendicular to the longitudinal axis of the vehicle to the upper end of an upright which extends vertically above a rear housing of the structure in which the internal combustion engine is housed. The lifting arm thus obstructs in its completely lowered position, the operator's view to the side, and to the rear, which poses problems, particularly as regards working safety.

2

The particular object of the present invention is to produce a lifting truck of the type defined above which is formed in such a way as to improve the operator's field of view.

According to the invention, this object is achieved by virtue of the fact that the internal combustion engine is disposed in a housing which is situated on the opposite side of the longitudinal axis to the cab and is spaced from the cab so as to define with the cab a space having a width at least equal to the width of the lifting arm, and by virtue of the fact that the lifting arm is articulated to the structure of the truck in such a position that, in its completely lowered position, it is partly accommodated in the space so as not to interfere with the view of the operator working in the driving cab.

Further characteristics and advantages of the truck according to the invention will become clear in the course of the detailed description which follows with reference to the appended drawings, provided by way of non-limiting example, in which:

Figure 1 is a side elevational view of a fork-lift truck;

Figure 2 is a front elevational view of the truck of Figure 1,

Figure 3 is a view of the truck of Figure 1 from above,

Figure 4 is a view similar to Figure 1 of a variant, and

3

Figure 5 is a perspective view of the vehicle shown in Figure 4.

With reference to Figures 1 to 3, a lifting truck, generally indicated 2, includes a support platform structure 4 provided with front and rear wheels 6 and 8 respectively, and with a telescopic lifting arm 22, articulated to the rear end of an upright 18 carried by the structure 4. The platform 4 supports a driving cab 10 situated on one side of the platform 4 and to one side of the longitudinal axis A-A of the truck.

On the opposite side of the axis A-A to the driving cab, the platform supports a housing 12 in which a longitudinally-extending internal combustion engine 16, provided with a vertically-directed exhaust pipe 20, is housed. The housing 12 is positioned at a distance from the cab 10 so as to define with the cab a space 14 which is at least as wide as the lifting arm 22.

The lifting arm 22 is articulated about a horizontal pin 22a transverse the axis A-A and situated at a level such that the arm is partly accommodated in the space 14 in its completely lowered position. In Figure 1, the telescopic arm 22 is illustrated in its completely retracted position, being shown in broken outline in a partially raised position, and in continuous outline in its completely lowered position in which it extends longitudinally adjacent the cab 10 in the space 14 and does not interfere with the view of the operator working in the driving cab. In particular, the top of the engine housing 12, the axis of the articulation pin 22a of the lifting arm, and the top of the lifting arm 22 in its completely

4

lowered position are all situated at a lower level than the line of sight of the operator working in the cab.

The lifting arm 22 is pivoted about the pin 22a by means of a hydraulic jack 24 the lower part of which is articulated at 24a to the central part of the platform 4. When the arm 22 is in the lowered position, the jack 24 is inclined forwardly and downwardly.

The inner slidable end element 26 of the telescopic arm 22 carries a head 28 to which an implement 32, which is pivoted by means of a jack 24, is articulated about a pin 30.

In the embodiment illustrated, the implement 32 is constituted by a forked platform; this platform may, however, be replaced by other types of implement, for example, by a bucket.

The variant illustrated in Figures 4 and 5 differs from the embodiment described above in that the jack 24 which causes the pivoting of the lifting arm 22 is articulated at the rear to the chassis of the truck about a pin 24 at the base of the upright 18, and is inclined forwardly and upwardly when the arm 22 is in the lowered position. Moreover, the exhaust pipe 20 is directed towards the rear part of the vehicle with a slight upward inclination, instead of being vertical.

By virtue of the characteristics of the truck according to the invention, not only the operator's view to the side and to the rear but also the

characteristics of <sup>5</sup> stability, manoeuvrability, accessibility, thrust force and habitability of the truck are improved. In fact, by virtue of the above-described positioning of the engine and the lifting arm, there is also a substantial lowering of the centre of gravity of the truck with obvious advantages in terms of its aforementioned characteristics and of its safety in use.

---

6  
CLAIMS

1. A lifting truck of the type comprising a wheeled structure carrying a lifting arm (22) articulated to the rear of the structure about a horizontal axis perpendicular to the longitudinal axis (A-A) of the truck, an internal combustion engine (16) supported by the structure for the propulsion of the truck and for the operation of the arm (22), and an operating and driving cab (10) situated on one side of the structure to one side of the longitudinal axis (A-A), characterised in that:

- the internal combustion engine (16) is disposed in a housing (12) which is situated on the opposite side of the longitudinal axis (A-A) to the cab (10) and is spaced from the cab so as to define with the cab a space (14) having a width at least equal to the width of the lifting arm (22),

- the lifting arm is articulated to the structure of the truck in such a position that, in its completely lowered position, it is partly accommodated in the space (14) so as not to interfere with the view of the operator working in the driving cab.

2. A lifting truck according to Claim 1, characterised in that the top of the engine housing (12), the articulation pin (22a) of the lifting arm (22) and the top of the lifting arm (22) in its completely lowered position are all situated at a lower level than the line of sight of the operator working in the cab (10).



FIG. 1  
1/3








FIG. 3



2/3


FIG. 2





# INTERNATIONAL SEARCH REPORT

International Application No PCT/EP 88/00647

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) *		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC <sup>4</sup> : B 66 F 9/065		
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>7</sup>		
Classification-System	Classification Symbols	
IPC <sup>4</sup>	B 66 F; B 60 P; B 66 C; E 02 F	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched *		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> *		
Category *	Citation of Document, <sup>11</sup> with Indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
Y	US, E, 30021 (OLSON) 5 June 1979, see abstract; figures 1-3 --	1, 2
Y	DE, A1, 2739537 (LOED CORP.) 9 March 1978, see page 9, paragraph 2; figures 1, 2 --	1, 2
A	FR, A1, 2287413 (THE LINER CONCRETE MACHINERY CO.) 7 May 1976 --	
A	FR, A1, 2545468 (KOEHRING CO.) 9 November 1984 --	
A	US, A, 4382743 (NEWELL) 10 May 1983 --	
A	US, A, 4345873 (WYMORE) 24 August 1982 -----	
<p>* Special categories of cited documents: <sup>10</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p>		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
5th September 1988		30 SEP 1988
International Searching Authority		Signature of Authorized Officer
EUROPEAN PATENT OFFICE		 P.C.G. VAN DER PUTTEN

**ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.**

EP 8800647  
SA 23404

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 22/09/88. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-E- 30021	05-06-79	US-A- 3836025	17-09-74
		DE-A- 2424682	12-12-74
		AU-A- 6856474	06-11-75
		GB-A- 1455952	17-11-76
		JP-A- 50019148	28-02-75
		CA-A- 1082652	29-07-80
DE-A- 2739537	09-03-78	None	
FR-A- 2287413	07-05-76	DE-A, B, C 2545427	29-04-76
		US-A- 4042135	16-08-77
		GB-A- 1528741	18-10-78
FR-A- 2545468	09-11-84	DE-A- 3416394	20-12-84
		GB-A, B 2144096	27-02-85
		US-A- 4632630	30-12-86
		CA-A- 1239620	26-07-88
US-A- 4382743	10-05-83	None	
US-A- 4345873	24-08-82	None	

EPO FORM 1009

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**